

# SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY INFORMATION

SDS # 01-GFS-01

#### MANUFACTURER

Morvillo Precision Products 160 Niantic Avenue Providence, RI 02907 (401) 353-7500

### MANUFACTURER EMERGENCY CONTACT

(401) 353-7500

### PRODUCT IDENTIFICATION TEXT

The information in this SDS is applicable to product codes for gold filled bonded stock with the following alloy #'s utilized as the gold layer: 4, 30, 35, 38, 58, 77, 80,90, 94, 96, 112, 88, 788, CFA, and M34. Information in this SDS represents the known health and safety hazards associated with these products and their components. The identity of specific components may be determined according to U.S. Department of Labor regulations [29CFR, Part 1910.1200(1)] or the applicable laws of other countries.

### PRODUCT IDENTIFICATION

**Product Name:** Karat Gold Filled Sheet

## 2. HAZARDS IDENTIFICATIONS

### **CLASSIFICATION**

These alloys are considered an "article" and are not hazardous in its solid form. However, certain processes such as cutting, milling, grinding, melting and welding could result in some serious hazardous materials being emitted. The GHS classification below pertains to these emitted products during these processes.

### LABEL SIGNAL WORD

Warning

### HAZARD STATEMENT

Copper may cause an allergic skin reaction. May cause damage to organs (Lung, central nervous system) through prolonged or repeated exposure. Nickel is suspected of causing cancer. May damage fertility or the unborn child. Hazardous to the aquatic environment. Avoid breathing dust/fume/gas/mist/vapors. Do not eat, drink or smoke when using this product. Avoid release to the environment

# **SYMBOLS**

Symbols	Hazard	GHS Classification	Hazard Statements
	Carcinogenicity	Category – 2	Suspected carcinogen. Nickel is suspected of causing cancer of the lungs and nasal cavities.
	Respiratory Sensitizer	Category – 1	Nickel may cause allergy or asthma symptoms or breathing difficulties if inhaled
	Toxic to Reproduction	Category – 1B	May cause genetic effects
	Specific Target Organ Toxicity (repeated exposure)	Category – 1	Copper may cause damage to lungs, blood and kidneys through prolonged or repeatedexposure
<b>(!</b> )	Skin Sensitizer	Category – 1	Nickel may cause allergic skin reaction.
***	Acute Toxic to Aquatic Life	Category – 1	Very toxic to aquatic life.
	Chronic Toxic to Aquatic Life	Category – 1	Very toxic to aquatic life with long lasting effects.

# POTENTIAL HEALTH EFFECTS

## **EYE**

Causes eye irritation.

## **SKIN**

Causes skin irritation. May cause skin discoloration.

#### INGESTION

Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause liver and kidney damage.

# **INHALATION**

Dust is irritating to the respiratory tract. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.

#### CHRONIC

Prolonged or repeated skin contact may cause dermatitis. May cause liver and kidney damage. May cause lung damage.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Ingredients</b>	<u>%</u>	CAS#	PEL#	TLV#
Gold	2.08-5.94	7440-57-5	N/A	N/A
Silver	0.30-0.50	7440-22-4	.01 mg/m3	0.1 mg/m3
Copper	83.58-87.45	7440-50-8	0.1 mg/m3	0.2 mg/m3
Zinc	8.94-10.0	7440-66-6	5 mg/m3	5 mg/m3 as ZnO
Nickel	0.0-0.05	7440-02-0	1.0 mg/m3	1.0 mg/m3

### 4. FIRST AID

#### **EYE CONTACT**

Check for and remove any contact lenses. Rinse thoroughly with clean water for at least 15 minutes. Do not use eye ointment. Seek medical attention immediately.

### SKIN CONTACT

Remove contaminated clothing, wash immediately with plenty of water for at least 5 minutes. Gently and thoroughly was the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient (moisturizing cream or lotion). If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

### **INHALATION**

Allow the victim to rest in a well-ventilated area. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

## **INGESTION**

Do not induce vomiting. If the subject is conscious, give milk or other form of soluble calcium such as limewater, calcium lactate, or calcium gluconate. Seek immediate medical assistance.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: CO2 and dry chemical

Unsuitable extinguishing media: Do not use water or halogenated extinguishing media. Do not use

water on molten metal: Explosion hazard could result.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed. Solid metal is not

flammable; however, finely divided metallic dust or powder may form an explosive mixture with air. In a fire, nickel may form nickel carbonyl, a highly

toxic substance and known carcinogen.

Special protective equipment and Self-contained breathing apparatus and full protective clothing

precautions for fire-fighters: must be worn in case of fire.

#### 6. ACCIDENTAL RELEASE MEASURES

# PERSONAL PRECAUTIONS

Avoid dust formation. Ensure adequate ventilation. Isolate spilled material and transfer to impervious containers. Avoid contact with skin, eyes, and mucous membranes. Wear protective clothing as described in Section 8 of this safety data sheet.

## METHODS AND MATERIALS

Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal. Collect dust using a vacuum cleaner equipped with HEPA filter. The vacuum cleaner should be explosion-proofed. If not possible, gently moisten dust before it is collected with shovel, broom or the like. This material and its container must be disposed of as hazardous waste. Keep out of water supplies and sewers.

### 7. HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment (See Section 8). Persons susceptible for allergic reactions should not handle this product. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with eyes, skin, and clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling

## **CONDITIONS FOR SAFE STORAGE**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs. Keep out of reach of children. Store away from incompatible materials (See Section 10).

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	OSHA Permissible Exposure Limit (PEL):	American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV):
Copper	0.1 mg/m³ TWA Fume 1 mg/m³ TWA dusts & mists	0.2 mg/m³ TWA Fume 1 mg/m³ TWA dusts & mists
Nickel	1 mg/m³ TWA	1.5 mg/m <sup>3</sup> TWA inhalable fraction A5
<u>Silver</u>	0.01 mg/m <sup>3</sup> TWA	0.1 mg/m <sup>3</sup> TWA dust 0.01 mg/m <sup>3</sup> TWA Soluble compounds
Gold	Not established	Not established
<u>Zinc</u>	Not established	Not established

### **ENGINEERING CONTROLS**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Ventilate as needed to control airborne dust. Use explosion-proof ventilation equipment if airborne dust levels are high. Special ventilation should be used to convey finely divided metallic dust generated by grinding, sawing etc., in order to eliminate explosion hazards. Follow the schedule for work place measurements when working with lead and its compounds.

### INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

#### **EYE/FACE PROTECTION**

Wear eye protection adequate to prevent eye contact with the product and eye injury from the hazards of cold working. Plastic-frame spectacles with side shields and filter lenses (shade #3 or #4) are recommended.

## SKIN PROTECTION

Wear appropriate protective gloves and clothing to prevent skin injuries from the hazards of cold working. Avoid flammable fabrics.

### **RESPIRATORY PROTECTION**

If an exposure level exceeds an OSHA PELs or other applicable standard, use an OSHA approved respirator having configuration (class, type of face piece, filter media, assigned protection factor, etc.) appropriate to the concentration of the contaminant(s) generated. For guidance on selection and use of respiratory protection, consult American National Standard Z88.2 (ANSI, New York, NY 10036 USA).

## **WORK/HYGIENIC PRACTICES**

To minimize the possibility of ingestion, wash hands and face before eating, drinking, applying cosmetics, or using tobacco.

# 9. PHYSICAL DATA AND CHEMICAL PROPERTIES

Appearance: Products are solid metals and are supplied in various shapes.

Color: varies from yellow, to green, and white.

Odor: Not Applicable pH: Not Applicable

Odor Threshold: Not Applicable

Boiling Point: 4215°F Melting Point: 1800°F

Evaporation Rate: Not Applicable

Flash Point: N/A

UFL%: Not Applicable Flammability: Not Flammable Vapor Pressure: Not Applicable

LFL%: Not Applicable

Relative Density: 8.90 (average) Vapor Density: Not Applicable

Solubility: Not Soluble Specific Gravity: No Data

Auto-Ignition Temp: Not Applicable Partition Coefficient: No Data Viscosity: Not Applicable

### 10. STABILITY AND REACTIVITY

### REACTIVITY

Low reactivity

## CHEMICAL STABILITY

Stable at normal conditions

### POSSIBILITY OF HAZARDOUS REACTIONS

Silver and copper can form unstable acetylides in contact with acetylene gas.

Hot molten material will react violently with water resulting in spattering and fuming.

# **CONDITIONS TO AVOID**

Contact with incompatible materials. Dust and fume clouds

Dust clouds may be explosive under certain conditions. Welding, burning, sawing, brazing, grinding or machining operations may generate dusts and fumes of metal oxides.

### INCOMPATIBLE MATERIALS

Strong oxidizers and halogens

## HAZARDOUS DESCOMPOSITION PRODUCTS

Toxic metal oxides are emitted when heated above the melting point.

### 11. TOXICOLOGICAL INFORMATION

### ROUTES OF EXPOSURE

## **EYE CONTACT**

Causes eye irritation.

#### SKIN

Causes skin irritation. May cause skin discoloration.

#### INGESTION

Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause liver and kidney damage.

#### **INHALATION**

Dust is irritating to the respiratory tract. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.

### SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

May cause irritation to mucous membranes. May cause skin and eye irritation. Coughing. Shortness of breath. Wheezing. The principal symptoms of lead poisoning are gastro-intestinal or central nervous system disturbances and anemia. Sensitization

### INFORMATION ON TOXICOLOGICAL EFFECTS

High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. When heated, the vapors/fumes given off may cause respiratory tract irritation. Overexposure of Tin can cause irritation of the eyes, skin, mucous membranes, and respiratory system. Acute overexposure to dust or fume can cause irritation of the eyes, nose, throat, and skin and under severe fume overexposure can cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. May cause skin and hair discoloration. Inhalation of copper dusts may change the gums and mucous lining of the mouth which is generally attributable to localized tissue effect rather than general toxicity

### MEASURE OF TOXICITY

COPPER	> 5,000  mg/kg*	Acute Oral

**NICKEL** > 9,000 mg/k\* Acute Oral

**SILVER** > 5,000 mg/kg\*\* Acute Oral

**ZINC** > 5410 mg/m3\* Acute Inhalation

GOLD No data available

# INGREDIENTS LISTED ON THE NATIONAL TOXICOLOGY PROGRAM(NTP)

Nickel (CAS 7440-02-0) Known to Be Human Carcinogen.

# INGREDIENTS LISTED ON THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

Nickel (CAS 7440-02-0) 2B Carcinogenic to humans.

### **ACUTE EXPOSURE**

Can cause metal fume fever, a metallic taste in the mouth, dryness or irritation of the throat, and coughing. After 4-48 hours symptoms can include sweating, shivering, headache, fever, muscle aches, nausea, vomiting, weakness and tiredness.

<sup>\*</sup> LD50, Mouse, Oral, \*\* LC50, Rat, Inhalation, 4 hour

### CHRONIC EXPOSURE

Chronic ingestion may damage the liver and kidneys. lungs, and blood,

# 12. ECOLOGICAL INFORMATION

These products should not be released into the environment. Compounds can be highly toxic to aquatic organisms. Metal dusts may migrate into soil and groundwater and be ingested by wildlife.

### 13. DISPOSAL CONSIDERATIONS

Do not discharge waste product into sanitary or storm sewers or allow it to contaminate soil. Dispose of in accordance with Federal, State and Local regulations

### 14. TRANSPORT INFORMATION

Not regulated as dangerous goods per USDOT. No special shipping or transportation requirements.

UN number Not applicable.

UN proper shipping name Not applicable.

Transport hazard class Not applicable.

Environmental hazards Not applicable.

Transport in bulk according to Annex II of Not applicable

MARPOL 73/78 and the IBC Code.

Special precautions Not applicable.

### 15. REGULATORY INFORMATION

#### US-OSHA (Hazard Communication Standard)

References: 29 CFR 1910.1200 Hazard Communication Standard

A finished casting is an article as defined in 29CFR 1910.1200 (c)

29 CFR 1910.1000 Air Contaminants

29CFR1910.1025 Lead

Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as cobalt, copper, iron, lead, manganese, nickel, tin, zinc and silica.

# **US-EPA** (Toxic Substances Control Act–TSCA)

All components of these products are on the TSCA inventory list or are excluded from listing.

#### **US-EPA (SARA Title III)**

Releases to the environment of Cobalt, Copper, Lead, Manganese, Nickel and Zinc (fume or dust) may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 16. OTHER INFORMATION

Last Updated: 01/31/2018

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).

Morvillo Precision Products